



Structural Fill SE250

Standard Specification Clause

Sundolitt Structural Fill SE250 Expanded Polystyrene (EPS). Large blocks of EPS with flame retardant additive for use as a lightweight fill in civil engineering applications. Manufactured and tested in accordance with BS EN 14933.

Compressive strength	250 kPa at 10% nominal compression
Design Load	100 kPa at 1% nominal compression
Thermal conductivity	0.033 W/mK
Block size	2400 x 1200mm



For the full range of physical properties please see our Structural Fill Datasheet on our website : www.sundolitt.com/en

Structural Fill SE250

- Manufacturer: Sundolitt Ltd
- Website: www.sundolitt.com/en
- Email: enquiriesuk@sundolitt.com
- Tel: +44 (0)1786 471586
- Fax: +44 (0)1786 464825
- Address: Sundolitt Ltd,
Suite A2 Stirling Agricultural Centre,
Stirling. FK9 4RN
- Product reference: Structural Fill SE250
- Thickness: 600 mm / 300 mm / 150 mm / 100 mm

Accreditation

Sundolitt Structural Fill SE250 EPS Blocks are manufactured in accordance with BS EN 14933 under Quality Control and Environmental Management Systems.



CONTACT US



01786 471586



enquiriesuk@sundolitt.com



www.sundolitt.com/en